

SAFETY VEST 40006

Product Description

- **Imported**
- Fluorescent Orange Safety Vest
- Class 2 ANSI/ISEA 107
- Two Inch Wide Fluorescent Yellow Stripes
- Zipper Front
- 100% Polyester
- Sizes: Medium to 3XLarge

Applications

Used by: pedestrians, workers, cyclists, motorcyclists, hunters and hikers.

Packaging

- Sold by each
- 36 Vests per Case

Care

Washable in warm water

Do not use Bleach



TECHNICAL INFORMATION

Federal law in the United States requires all personnel working on a federally funded highway to wear a high-visibility vest starting on November 25, 2008.

Minimum areas of visible material – ANSI/ISEA 107-2010

	Performance Class 3	Performance Class 2	Performance Class 1
Background material	1240 in ² (0.80 m ²)	775 in ² (0.50 m ²)	217 in ² (0.14 m ²)
Retroreflective or combined-performance material used in conjunction with background material	310 in ² (0.20 m ²)	201 in ² (0.13 m ²)	155 in ² (0.10 m ²)
Combined-performance material used without background material	NA	NA	310 in ² (0.20 m ²)
Minimum width of retroreflective material	2 in (50 mm)	1.375 in (35 mm)	1 in (25 mm) or 2 in (50 mm) combined-performance material (without background material)
Minimum number of yards per retroreflective material width	4.3 yds of 2 in (50 mm) width	4 yds of 1.375 in (35 mm) width 2.8 yds of 2 in (50 mm) width	4.3 yds of 1 in (25 mm) width 3.1 yds of 1.372 in (35 mm) width 2.15 yds of 2 in (50 mm) width
Photometric performance	Level 2 (Table 4) or Level 1 (Table 5)	Level 2 (Table 4) or Level 1 (Table 5)	Level 2 (Table 4) or Level 1 (Table 5)

	Med	Large	XL	2XL	3XL
	40006	40007	40008	40009	40010
Pack	36	36	36	35	36
Case	23.0	23.0	23.0	23.0	23.0
	14.0	14.0	14.0	14.0	14.0
	7.5	7.5	7.5	7.5	7.5
Cu Ft.	1.4	1.4	1.4	1.4	1.4
Lb.	20	21	23	24	26